



EDITION **2/2023**











Open your **dreams...** and find your **style**

Nowadays, we live in a constant rush, trying to find peace, beauty, and a safe refuge at home and other places where we spend our time. A sense of security and harmony improves the everyday quality of life. INVADO understands and respects those needs. Being one of the most rapidly developing manufacturers of door joinery and skirting boards in Poland, we do our best to give you products that meet your needs, with high, individual aesthetics, and the best possible functional features. Our market position is built on over thirty years of experience and continuous investment in technology, people, and quality improvement.

NVADS

months of warranty on INVADO products]]]]]]]]

Quality above all

The belief that quality is of the utmost importance remains the common denominator of the design phase and the entire production process at INVADO. This is confirmed, among others, by the ISO 9001 Certificate, which ensures that all our products meet high European standards. The guarantee of the guality of products and services, in addition to the price and timeliness of deliveries, is the basic goal of the company, enabling it to be perceived as a trusted partner.

INVADO Technology

Production of door leaves and door frames is the strongest point of our INVA-DO offer, therefore the implementation of innovative production technology of foiled doors (INVADO Technology) became a breakthrough in the Company's activity. The most distinct feature of this technology is foiling surfaces without connecting foil on rebate edges. Because of this method, the edge of a door leaf looks aesthetically clean and is also more resistant to damage. It's very unlikely to break off the foil because it ends in the inner corner of the rebate-invisible to the eye. "Technology of foiling flat doors in the mass production system" has been in use since 2007 when it comes to all foiled doors. In addition-off-rebate foiling creates rounded edges in INVADO door leaves, safe for the hands of adults and children. Nowadays, thanks to the innovative method of door production, INVADO is among the most technologically advanced companies in Europe.

Hygienic certificates

Hygienic certifications aim to prevent materials and products hazardous to health and life to be introduced to the public or limit the acceptable range and application methods to eliminate health risks. All INVADO products have hygienic certificates:

- interior door frames in artificial veneer No. 441/322/451/2017
- interior door leaves in artificial veneer or flat lacquered No. 348/322/353/2020
- skirting boards in artificial veneer No. 256/322/261/2019

Technical Approvals and National Technical Assessments

Technical Approvals and National Technical Assessments, issued by the Building Research Institute, are decisions that grant the use of building materials and products. In accordance with the Construction Products Act of April 16th 2004, as amended (unified text: Journal of Laws of 2016, item 1570), the products to which the Technical Approvals and National Technical Assessments relate, may be placed on the market and can be used in construction. INVADO Company assessed and verified the constancy of performance, made a national declaration of performance, and labeled the products with a construction mark in accordance with applicable regulations. INVADO's Technical Approvals and National Technical Assessments:

- Interior flat and glass doors—ITB-KOT-2017/0313 edition 2;
- Modular interior doors—ITB-KOT-2017/0003 edition 2;
- Folding, swinging, and sliding interior doors—ITB-KOT-2018/0296 edition 1;
- Technical doors GUARDIA EI,30 and EI,60 (wooden interior entrance doors of HALSPAN system)-ITB-KOT-2018/0407 edition 1; National Certificate Of Stable Performance AC 158-UWB-W1355;
- Technical doors IGNIS—National Certificate Of Stable Performance . AC 158-UWB-W3479;
- Interior entrance doors EGIDA with increased resistance to breaking-in-ITB-KOT-2018/0598 edition 1;
- Adjustable door frames for interior doors—ITB-KOT-2019/1221 edition 2;
- Block door frames for interior doors OB3 type P-ITB-KOT-2017/0312 edition 2;
- Door frames SARA-PRO for interior doors—ITB-KOT-2019/1076 edition 1;
- Metal door frames—ITB-KOT-2021/2091 edition 1; .
- Housing system for metal door frames—ITB-KOT-2019/1221 edition 1.





CERTIFICATES AND AWARDS



BRAND OF THE DECADE 2009-2019 GOOD BRAND 2019 and 2021

An independent group of experts confirmed that products bearing the INVADO logo are characterized by: quality, trust, and reputation, awarding

our company the title of BRAND OF THE DECADE 2009-2019 and the titles of GOOD BRAND 2019 and GOOD BRAND 2021. We would like to thank our customers for the trust you place in us by choosing INVADO doors for their dream interiors, our Business Partners for fruitful cooperation, recommending, and support, and all INVADO Employees for jointly building a good brand at every stage of its creation. We are incredibly grateful that our hard work is appreciated and we look forward to the future with pride.



CONSUMER'S LAUREL

INVADO brand has been recognized by Polish consumers and honored with the prestigious Consumer's Laurel emblem.



The VOC certification tests the emission of volatile organic compounds released from the facility and, depending on the results obtained, the tested sample is assigned a class, ranging from A+ (best)

to C (worst). The possession of the VOC certificate confirms that the product does not release harmful to health substances inside the house, such as formaldehyde and benzene—carcinogenic elements that unfortunately are often contained in paints, and materials used on windows.



ISO 9001

The INVADO Company applies to the Quality Management System and fulfills the requirements of PN-EN ISO 9001 in the scope of designing, production, and sale of furniture components and finishing profiles, interior doors made of wood and wood-based materials, and technical doors.

FSC™



Control of Product Origin and environmental protection are the leading elements of INVADO's development strategy. This is confirmed by an international certificate issued by the Forest Stewardship Council[™] and obtained by the company in 2007.

The mark of responsible forestr

Ask for FSC[™] certified products in our range.



UNIA EUROPEJSKA

CERTIFICATE RESOURCES SAVED

INVADO has obtained the international certificate in waste management and recycling issued by INTERSEROH zero waste solutions.





News

The White

P

PAGE 90

DECORATO 12

AVANT-GARDE STYLE

We invite you to interiors inspired by **INVADO milled doors**. We present a harmonious combination of classics and modern design solutions—the **Belgatto** and **Decorato** collections. Mills—previously associated rather with classic design—have gained a completely new, fresh character, thanks to our designers. We recommend them for interiors where there is no room for boredom and clichéd arrangement ideas.

the Belgatto and Decorato collection

PAGE 88

3elgatto 14

With a black dot above the "i"

You don't need much to create an interior with character. The door with a **black panel**, which

serves as an original decorative form, will be perfect as an arrangement of the dot above the "i". It perfectly corresponds with both the timeless white veneer, the classic color of European Oak, and Naturo Oak for those who miss the retro or fusion style.



BLACK PANEL IN CORATO, AVERSA, TAMPARO, AND LINEA FORTE DOOR LEAVES











Good news for lovers of minimalism. Door leaves dedicated to modern and elegant interiors in combination with the invisible **SARA-PRO door frame, now available in even more colours.** The colour collection includes as many as 15 colours that will allow you to perfectly match the door to your interior.

PAGE 130

IN ADDITION TO THE NEW COLOURS, THE HIDDEN DOOR IS AVAIL-ABLE IN A VERSION PREPARED FOR PAINTING OR WALLPAPERING.

.

Table of contents



+

GOOD TO KNOW	8–10
GLASS TYPES	11
DECOR PALETTE	12–15
COLLECTION OF MODULAR DOORS	16–57
COLLECTION OF FOILED DOORS	58–85
MODERN AND OPTIMO LINE COLLECTION	86–107
COLLECTION OF GLASS DOORS	108
COLLECTION OF FOLDING DOORS	110
SLIDING SYSTEMS	
POCKET DOOR sliding system	112
WALL-MOUNTED sliding system	114
TECHNICAL DOORS	
EGIDA interior entrance doors	116
IGNIS fire doors	118
GUARDIA fire doors	120
TECHNICAL INFORMATION	122
DOOR FRAMES	
BLOCK door frame	125
ADJUSTABLE door frame (REBATED)	126
ADJUSTABLE door frame (NON-REBATED)	127
METAL door frames	128
Concealed door frame SARA-PRO	130
Housing system for metal door frames	132
ACCESSORIES	133–135
HANDLES	136
SKIRTINGS	138

COLLECTION OF **MODULAR** DOORS

collection Corato	18	collection Artano 20	collection Aversa	20	collection Mirror	22	collection Lago	24	collection Pasaro 26	collection Vinadio	28	collection Fossano 30	
							2					8-	
collection Imperia	32	collection Destino Unico 34	collection Livata	36	collection Versano	38	collection Nogaro	40	collection Tamparo 42	collection Linea Forte	44	collection Capena Inserto 46	
												Ar	
collection Martina	48	collection Domino 50	collection Bianco	52	collection Larina	54	collection D'Artagnan	56					
							d.						

COLLECTION OF **FOILED** DOORS

collection Salerno	60	collection Norma Decor 62, 92, 104	collection Torino	64	collection Merano	66, 102	collection Lido	68, 94, 106	collection Dolce	70, 96	collection Strada	72	collection Sagittarius	74
		-			4		4.		-		-			
collection Gemini	76	collection Virgo 78, 98	collection Parma	80	collection Orso	82, 100	collection Libra	84	collection Taurus	84				
							į,							

FOILED AND MODULAR DOORS

FOILED DOORS

Visually, **foiled doors** are lighter than modular ones, which is combined with their stability. Their construction is a frame made of MDF board with a "honeycomb" or tubular chipboard (charged extra) filling. The frame with the filling is covered with a 3 mm-thick HDF board from both sides and wrapped with a decorative foil. The glazing beads of different profiles are used to hold the filling elements in these doors.






MODULAR DOORS


Construction of **modular** doors: two vertical elements, upper and lower horizontal elements. Filling: MDF panels of different thicknesses or glass 4 mmthick. For each model you can select a decorative foil. Glass and other filling elements in these door leaves are not installed using glazing beads, but with all the construction elements at once, which greatly improves their stability.





REBATED AND NON-REBATED DOORS






The edge of **a rebated door** leaf is finished with a rebate (visible in the picture A1) that overlaps a door frame when the door is closed. Door leaves made this way do not fit flush with a door frame.

The edge of **a non-rebated** door leaf has a flat surface. Door leaves made this way fit flush with a door frame (A2).

LEFT AND RIGHT DOOR

Before buying doors, it is worth considering in which direction they should open. For safety reasons, bathroom or kitchen doors should be installed in a way that makes it possible to open them outwards. In other areas, it is dependent on users' preference and the layout of the apartment or house.

The next step is to determine what kind of doors we are looking for; right or left doors. What does that mean? If the hinges are installed on the right side of a door frame, it means we need a right door, if the opposite—we have to choose the left door. Therefore, before going to the store it is worth reconsidering this question and writing down a list of needed right and left doors and to determine the opening direction for each of them.




DOOR PRICE CALCULATION

In most cases, the quoted prices are for a door leaf without a door frame and door handles. To obtain the full price of the door set, you have to use the following calculation:




LEGEND

Please note the annotations marked with the following icons. They contain important information related to the door leaf models.




FOIL-TYPES OF WOOD TEXTURE (GRAINING)


Structures of INVADO foils can be divided into 3 categories:



UNIDIRECTIONAL FOIL WITH VERTICAL TEXTURE: Most INVADO foils are available in this type of texture. Exceptions: Chestnut (ENDURO), Italian oak, and Severo oak (ENDURO 3D).



UNIDIRECTIONAL FOIL WITH HORIZONTAL TEXTURE: Currently, there are two foils with this texture in the INVADO offer. These are: Italian oak and Severo oak (ENDURO 3D).



BIDIRECTIONAL FOIL WITH VERTICAL AND HORIZONTAL TEXTURE: The combination of two previous types of texture. There is one foil of that type in the INVADO offer—Chestnut (ENDURO).



DOOR EDGE COLOUR



Due to the manufacturing technique, for doors from the OPTIMO LINE collection, it is possible to use the edge of the leaf in a different colour than its surface. The base for creating unique creations is the edge in the colour: black, alpine white, or natural Hamilton oak in combination with the OPTIMO LINE colour palette (p. 13)

DOOR EDGE COLOUR	DOOR COLOUR
B726 black	COLOUR PALETTE FOR OPTIMO LINE (p. 13)
B688 alpine white	COLOUR PALETTE FOR OPTIMO LINE (p. 13)
8717 natural hamilton oak	B687 B688 aloine white (n 13)

B717 natural hamilton oak

B687, B688 alpine white (p. 13)



INDIVIDUAL BATCHES OF GLASS MAY VARY IN SHADE

satinato



chinchilla



transparent



DECOR PALETTE

DUE TO THE PRINTING TECHNIQUE, THE COLOURS OF THE PRODUCTS PRESENTED IN THE CATALOGUE MAY DIFFER FROM THE ORIGINAL

ENDURO

ENDURO classification: Foil of high-quality design and a very good imitation of a natural wood structure. High durability. Intended for: buildings and living quarters with a wide range of use.



ENDURO 3D

Three-dimensional reproduction of the wood structure and high durability.

www.invado.pl precious oak B541 classic walnut B597 ashy oak B598 anthracite B637 italian oak B639 B657 european oak B656 severo oak

UNIDIRECTIONAL FOIL (HORIZONTAL)

ENDURO PLUS

Extended group of decors with high value, tactile structure and very high durability.













intensity of use: $\bullet \bullet \circ \circ \circ$



BIDIRECTIONAL FOIL (VERTICAL + HORIZONTAL)

intensity of use: $\bullet \bullet \circ \circ \circ$



ECO-VENEER FORTE

ECO-VENEER laminate **CPL** ••••• intensity of use: $\bullet \bullet \circ \circ \circ$


ECO-VENEER FORTE classification — high-quality laminate in modern colours, very high durability. CPL — foil in modern colours. Intended for: hotels, offices, public buildings.



LAMINATE CPL 0.15 mm / 0.8 mm

intensity of use: 0.15 mm: • • • • • 0 0.8 mm: • • • • •

Maximum strength decors, dedicated exclusively to the OPTIMO LINE door collection. Available in 2 thicknesses: 0.15mm (door leaves and frames), 0.8mm (door leaves)



ENDURO POLI

polar pine



B747

0.15 mm



intensity of use: $\bullet \bullet \bullet \bullet \circ$

Classification ENDURO POLI: high-quality polypropylene foil is characterised by excellent durability

Intended for: buildings and living quarters with a wide range of use.

Only available as a door frame colour for:

- BLOCK DOOR FRAMES, • •
- ADJUSTABLE DOOR FRAMES FOR REBATED DOORS,
- ADJUSTABLE DOOR FRAMES FOR NON-REBATED DOORS.

Can be combined with all models and colours of interior modular and foiled INVADO doors.

CUSTOM COLORS

DUE TO THE PRINTING TECHNIQUE, THE COLOURS OF THE PRODUCTS PRESENTED IN THE CATALOGUE MAY DIFFER FROM THE ORIGINAL

CPL 0.15 mm and CPL 0.8 mm decors in NCS colours available for individual requests.

CPL 0.15 mm and CPL 0.8 mm decors i	n NCS colours available for individual rec	quests.		
NCS S0907-Y30R	NCS 51060-Y10R	NCS 50560-G90Y	NCS S1505-Y50R	NCS 52060-Y10R
Cotton Beige	Brilliant Yellow	Citrus Yellow	Sand Beige	Curry Yellow
NCS S3502-Y	NCS 50502-Y50R	NCS 55040-R	NCS S1580-Y90R	NCS 53060-R
Pebble Grey	Came Beige	Burgundy Red	China Red	Chilli Red
NCS 57010-R30B	NCS S1030-R80B	NCS 53060-R90B	NCS S850S-R80B	NCS S0907-Y30R
Aubergine Purple	Horizon Blue	Delft Blue	Indigo Blue	Kiwi Green
NCS S1060-G40Y	NCS 55030-B30G	NCS 52005-Y60R	NCS 51500-N	NC5 52000-N
Lime Green	Niagara Green	Cashmere Grey	Silk Grey	Light Grey
NCS 54005-Y50R	NCS 55000-N	NCS 57005-Y20R	NCS 52005-Y20R	NCS S6005-Y20R
Stone Grey	Dust Grey	Lava Grey	Taupe Grey	Cubanit Grey
NCS 51000-N	NCS 54500-N	NCS 58500-N	NCS 56500-N	NCS 58000-N
White Grey	Arctic Grey	Solid Soft Black	Onyx Grey	Graphite Grey
NCS S9000-N	NCS 50502-G50Y	NCS 50300-N	NCS 50500-N	NCS 50500-N
Black	Cream White	Platinum White	Premium White ST22	Premium White Solid

Details on a non-standard offer should be arranged with the appropriate market manager — see page 140.



CPL 0.15 mm and CPL 0.8 mm decors available for individual requests.

			CPL 0.15 mm and CPL 0.8 mm c	lecors available for individual requests.
Dark Grey Chicago Concrete	Natural Mandal Maple	Metallic Inox	Aluminium	Black Gold Metal Slate
Grey-Beige Bamenda	Natural Bardolino Oak	Grey Arizona Oak	Navarra Ash	Natural Brown Branson Robinia
Truffle Brown Branson Robinia	Light Lakeland Acacia	Natural Wild Oak	Light Sorano Oak	Graphite Denver Oak
Ellmau Beech	Verona Cherry	Lincoln Walnut	Mali Wenge	Shorewood
Grey Corbridge Oak	Vincenza Oak	Grey Vincenza Oak	Natural Kendal Oak	Anthracite Fineline Metallic
Natural Dijon Walnut	Natural Corbridge Oak	White Aland Pine	Natural Pacific Walnut	Natural Hickory
White Fleetwood	Champagne Fleetwood	Lava Grey Fleetwood	Premium White ST19	
		non-standard offer should l the appropriate market mar — see page 140.		

COLLECTION OF MODULAR DOORS

Corato	18
Artano	20
Aversa	20
Mirror	22
Lago	24
Pasaro	26
Vinadio	28
Fossano	30
Imperia	32
Destino Unico	34
Livata	36
Versano	38
Nogaro	4(
Tamparo	42
Linea Forte	44
Capena Inserto	46
Martina	48
Domino	50
Bianco	52
Larina	54
D'Artagnan	56






COLLECTION OF MODULAR DOORS



DOOR LEAVES OPTIONS







4

3

2

CONSTRUCTION

2

rebated

rebated

-hon

1 filling element: 22 mm thick panel

filling element: panel or glass depending on the model (4 mm thick). Model 6 has black panels in B726

the frame is made of an MDF board: upper part of the frame is 350 mm high, lower part of the frame is 400 mm high

4 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
additional hinge for the non-rebated door—included in a door frame	ie
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60""100"	
Additional information: equipment and accessories	P. 133–137

GLASS






Artano and Aversa

COLLECTION OF MODULAR DOORS

Rebated Artano 2 in B462



DOOR LEAVES OPTIONS







4

3

CONSTRUCTION

1 filling element: 16 mm thick panel

2 filling element: panel or glass depending on the model (4 mm thick). Aversa 3 has a black panel in B726

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

side edges and upper edge are foiled

- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
additional hinge for the non-rebated door—included in a door france	me
caps for hinges (chrome, satin chrome, golden, black)—set for 1 his	nge unit
ventilation undercut	
PVC ventilation sleeves	
• metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

rebated

ebated

-40

•	lock 72 mm for	a standard key	, a WC knob,	, or a cylinder	lock insert
---	----------------	----------------	--------------	-----------------	-------------

- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129


GLASS



COLLECTION OF MODULAR DOORS



DOOR LEAVES OPTIONS





22





CONSTRUCTION

1 filling element: 6 mm thick panel

2 filling element: mirror (4 mm thick)

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated

rebated

-40

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129





ADDITIONAL OPTIONS

1

2

3

4


door without a keyhole	no extra charge
• door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• additional hinge for the non-rebated door—included in a door fram	ne
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ige unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
• aluminium threshold, widths "60"–"100"	
Additional information: equipment and accessories	P. 133–137

Lago

COLLECTION OF MODULAR DOORS



DOOR LEAVES OPTIONS









3

Lago 3





CONSTRUCTION

2

rebated

ebated

-40

1 filling element: 22 mm thick panel

filling element: panel or glass, depending on the model (4 mm thick)

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

side edges and upper edge are foiled

STANDARD EQUIPMENT

- rounded vertical edges of door leaves (more info on p. 122) •
- double door leaves have a rebate and a counter-rebate (drawing on p. 122) .
- width of single doors: "60"-"100" / width of double doors: "120"-"200" .

ADDITIONAL OPTIONS

2

door without a keyhole	no extra charge
door width "100"	no extra charge
door width "100"	
 additional hinge for the door in sizes "60"-"80" 	
additional hinge for the non-rebated door—included in a door fram	ne
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133-137

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100" $\,$
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS






Pasaro

COLLECTION OF MODULAR DOORS



DOOR LEAVES OPTIONS









3

1



CONSTRUCTION

1 filling element: 22 mm thick panel

filling element: panel or glass, depending on the model (4 mm thick)

the frame is made of an MDF board: upper part of the frame is 350 mm high, lower part of the frame is 400 mm high
door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
• additional hinge for the non-rebated door—included in a door fra	ime
caps for hinges (chrome, satin chrome, golden, black)—set for 1 h	iinge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
• aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
 screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

STANDARD EQUIPMENT

rebated

ebated

-40

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS






Vinadio

COLLECTION OF MODULAR DOORS



DOOR LEAVES OPTIONS





28



4

3

CONSTRUCTION

2

rebated

ebated

-40

1 filling element: 22 mm thick panel

filling element: panel or glass, depending on the model (4 mm thick)

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

Vinadio 3

door without a keyhole	no extra charge
door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• additional hinge for the non-rebated door—included in a door fran	ne
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hir	nge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
• aluminium threshold, widths "60""100"	
Additional information: equipment and accessories	P. 133–137

GLASS






Fossano

COLLECTION OF MODULAR DOORS



DOOR LEAVES OPTIONS





30



CONSTRUCTION

2

rebated

rebated

-hon

1 filling element: 22 mm thick panel

filling element: panel or glass, depending on the model (4 mm thick)

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

• side edges and upper edge are foiled

STANDARD EQUIPMENT

- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

4

3

• width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
• additional hinge for the non-rebated door—included in a door fra	ime
caps for hinges (chrome, satin chrome, golden, black)—set for 1 hi	inge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
• metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
 screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES


 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS




Imperia

COLLECTION OF MODULAR DOORS



DOOR LEAVES OPTIONS





32







3

mperia 3





CONSTRUCTION

1 filling element: 22 mm thick panel filling element: panel or glass dependi

filling element: panel or glass, depending on the model (4 mm thick)

the frame is made of an MDF board: upper part of the frame is 350 mm high, lower part of the frame is 400 mm high

4 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
 rounded vertical edges of door leaves (more infi
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

1

2

door without a keyhole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
additional hinge for the non-rebated door—included in a door frame	me
caps for hinges (chrome, satin chrome, golden, black)—set for 1 hi	nge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
• aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

STANDARD EQUIPMENT

rebated

ebated

-40

- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS




Destino Unico

COLLECTION OF MODULAR DOORS



DOOR LEAVES OPTIONS







2

3

4

5



One of the most popular models of INVADO doors—DESTINO UNICO—has been awarded a "Gold Medal". These door leaves make a bold combination of colours which allows the creation of intriguing, stylized interiors.

Therefore, we did not doubt that this was the most suitable collection to be submitted to the prestigious "Gold Medal" contest, held at the International Poznań Fair BUDMA. The IPF "Gold Medal" is one of the most recognizable awards in the Polish market, which is given to innovative products of the highest quality. We are proud of this achievement and we would like to thank all those involved in the production and sales of our Destino Unico doors.

CONSTRUCTION

- filling element: panel or glass, depending on the model (4 mm thick)
- 2 filling element: 22 mm thick panel
- 3 the frame is made of an MDF board

STANDARD EQUIPMENT

ebated

ebated

-40

- 4 double-sides glass insert—80 mm wide
- 5 door leaf covered with ENDURO foil or ECO-VENEER
- side edges and upper edge are foiled
 rounded vertical edges of door leaves (more info on
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
door width "100"	5
additional hinge for the door in sizes "60"-"80"	
additional hinge for the non-rebated door—included in a door frar	me
caps for hinges (chrome, satin chrome, golden, black)—set for 1 hinge unit	
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
 - screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
 - magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
 - hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS




Livata

COLLECTION OF MODULAR DOORS



DOOR LEAVES OPTIONS









3





CONSTRUCTION

1 filling element: 22 mm thick panel

2 filling element: panel or glass, depending on the model (4 mm thick)

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

2

1

door without a keyhole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
additional hinge for the non-rebated door—included in a door fra	ime
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 h	inge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

rebated

ebated

-40

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert	t
---	---

- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS




the glossy side of glass is on the hinge side

37

Versano

COLLECTION OF MODULAR DOORS









CONSTRUCTION

1 filling element: 22 mm thick panel filling element: panel or glass dependent

filling element: panel or glass, depending on the model (4 mm thick)

the frame is made of an MDF board: upper part of the frame is 350 mm high, lower part of the frame is 400 mm high

door leaf covered with ENDURO foil or ECO-VENEERside edges and upper edge are foiled

- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

4

3

• Width of single doors. 00 = 100 / Width of double doors. 120 = 20

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
door width "100"	
• additional hinge for the door in sizes "60"-"80"	
additional hinge for the non-rebated door—included in a door frar	ne
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	nge unit
ventilation undercut	
PVC ventilation sleeves	
• metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

 screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

• lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

STANDARD EQUIPMENT

rebated

rebated

-LOU

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS




Nogaro

COLLECTION OF MODULAR DOORS













3

Nogaro 3

1

2





CONSTRUCTION

2

rebated

ebated

-40

1 filling element: 22 mm thick panel

filling element: panel or glass, depending on the model (4 mm thick)

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
additional hinge for the non-rebated door—included in a door fran	ne
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hir	nge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"—"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129


GLASS



Tamparo

COLLECTION OF MODULAR DOORS











3

Tamparo 3



Tamparo 4 NEW

CONSTRUCTION

1 filling element: 22 mm thick panel

filling element: panel or glass, depending on the model (4 mm thick). Model 4 has black panels in B726 2

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled rounded vertical edges of door leaves (more info on p. 122) •
- .
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200" .

ADDITIONAL OPTIONS

2

1

door without a keyhole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
additional hinge for the non-rebated door—included in a door fran	ne
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hir	nge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

rebated

ebated

-40

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100" $\,$
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
 [ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide 	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129


GLASS



Linea Forte

COLLECTION OF MODULAR DOORS









1

CONSTRUCTION

1 filling element: 22 mm thick panel

2 filling element: panel or glass, depending on the model (4 mm thick). Models 7 and 8 have black panels in B726

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

4

3

• width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• additional hinge for the non-rebated door—included in a door fra	me
caps for hinges (chrome, satin chrome, golden, black)—set for 1 hi	inge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"—"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

rebated

rebated

-40

	lock 72 r	nm for a	standard	kev, a	WC knob,	or a d	vlinder	lock inse	rt

- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES


 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS




Capena Inserto

COLLECTION OF MODULAR DOORS



DOOR LEAVES OPTIONS





46



2

4

5

3

CONSTRUCTION

filling element: panel or glass, depending on the model (4 mm thick)

- 2 filling element: 22 mm thick panel
- 3 the frame is made of an MDF board

4 ALU strip—8 mm

door leaf covered with ENDURO foil or ECO-VENEERside edges and upper edge are foiled

- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated

rebated

-40

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

data Mina data kala		
door without a keyhole	no extra charge	
door width "100"		
• additional hinge for the door in sizes "60"-"80"		
• additional hinge for the non-rebated door—included in a door fram	ne	
caps for hinges (chrome, satin chrome, golden, black)—set for 1 hinge unit		
ventilation undercut		
PVC ventilation sleeves		
metal ventilation sleeves, round (chrome, golden)		
metal ventilation sleeves, square (chrome, nickel)		
door made in a non-rebated version for sliding systems		
door made in non-rebated version		
double door		
cylinder lock insert 31/36 (31/31 in non-rebated door leaves)		
• automatic bottom door seal, widths "60"-"100"		
• aluminium threshold, widths "60"-"100"		
Additional information: equipment and accessories	P. 133–137	


GLASS



Martina

COLLECTION OF MODULAR DOORS









1

CONSTRUCTION

1 filling element: 22 mm thick panel

2 filling element: panel or glass, depending on the model (4 mm thick)

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

• side edges and upper edge are foiled

STANDARD EQUIPMENT

rebated

ebated

-40

- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

4

3

• width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge	
door width "100"		
• additional hinge for the door in sizes "60"-"80"		
additional hinge for the non-rebated door—included in a door fram	ie	
caps for hinges (chrome, satin chrome, golden, black)—set for 1 hinge unit		
ventilation undercut		
PVC ventilation sleeves		
metal ventilation sleeves, round (chrome, golden)		
metal ventilation sleeves, square (chrome, nickel)		
door made in a non-rebated version for sliding systems		
door made in non-rebated version		
double door		
cylinder lock insert 31/36 (31/31 in non-rebated door leaves)		
automatic bottom door seal, widths "60"-"100"		
aluminium threshold, widths "60"-"100"		
Additional information: equipment and accessories	P. 133–137	

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES


 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129


GLASS



Domino

COLLECTION OF MODULAR DOORS









1

2

KONSTRUKCJA

2

rebated

rebated

-hon

1 filling element: 10 mm thick panel

filling element: panel or glass, depending on the model (4 mm thick)

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

side edges and upper edge are foiled

- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

4

3

• width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
additional hinge for the non-rebated door—included in a door fra	me
caps for hinges (chrome, satin chrome, golden, black)—set for 1 hi	nge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
door made in non-rebated version	
double door	
cylinder lock insert 31/36 (31/31 in non-rebated door leaves)	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

GLASS






COLLECTION OF MODULAR DOORS




DOOR LEAVES OPTIONS



DECORS



52



1

2

4

3

CONSTRUCTION

2

rebated

rebated

-LOU

1 filling element: 33 mm thick panel

filling element: panel (10 mm thick) or glass (4 mm thick) depending on the model

3 the frame is made of an MDF board

4 door leaf covered with ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS


door without a keyhole	no extra charge	
door width "100"		
additional hinge for the door in sizes "60"-"80"		
additional hinge for the non-rebated door—included in a door fram	ne	
caps for hinges (chrome, satin chrome, golden, black)—set for 1 hinge unit		
ventilation undercut		
PVC ventilation sleeves		
metal ventilation sleeves, round (chrome, golden)		
metal ventilation sleeves, square (chrome, nickel)		
door made in a non-rebated version for sliding systems		
door made in non-rebated version		
double door		
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)		
automatic bottom door seal, widths "60"-"100"		
aluminium threshold, widths "60"-"100"		
Additional information: equipment and accessories	P. 133–137	

GLASS




Larina

COLLECTION OF MODULAR DOORS











1

2

4

3

CONSTRUCTION

2

rebated

rebated

I-LIOU

1 filling element: 35 mm thick panel

filling element: panel (10 mm thick) or glass (4 mm thick) depending on the model

3 the frame is made of an MDF board

4 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled .
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm • for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

door without a keyhole	no extra charge	
door width "100"		
• additional hinge for the door in sizes "60"-"80"		
additional hinge for the non-rebated door—included in a door fram	ne	
caps for hinges (chrome, satin chrome, golden, black)—set for 1 hinge unit		
ventilation undercut		
PVC ventilation sleeves		
metal ventilation sleeves, round (chrome, golden)		
metal ventilation sleeves, square (chrome, nickel)		
door made in a non-rebated version for sliding systems		
door made in non-rebated version		
double door		
• cylinder lock insert 31/36 (31/31 in non-rebated door leaves)		
automatic bottom door seal, widths "60"-"100"		
aluminium threshold, widths "60""100"		
Additional information: equipment and accessories	P. 133–137	

GLASS





D'Artagnan

COLLECTION OF MODULAR DOORS









CONSTRUCTION

1

rebated

ebated

-40

D'Artagnan 1

frame is made of finger joint pinewood, covered with MDF and HDF boards

2 filling element: panel (10 mm thick) or glass (6 mm thick) depending on the model 3

- 3 door leaf covered with ENDURO foil or ECO-VENEERside edges and upper edge are foiled
 - rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
• door width "100"	
• additional hinge for the door in sizes "60"-"80"	
additional hinge for the non-rebated door—included in a door fram	ne
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ige unit
ventilation undercut (INTERO model)	
door made in non-rebated version	
double door	

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: equipment and accessories

D'Artagnan 7 TONDO

STANDARD EQUIPMENT

•	lock 72 mm	for a standard ke	y, a WC knob,	, or a cylinder	lock insert
---	------------	-------------------	---------------	-----------------	-------------

- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS

sat

the matt (engraved) side of glass is located on the hinge side

tinato		transparent		engi
4	no extra charge	-	no extra charge	

engraving—7 TONDO only

no extra charge

P. 133-137

longer execution time

longer execution time

FOILED DOORS

Salerno	
Norma D	ecor
Torino	
Merano	
Lido	
Dolce _	
Strada	
Sagittari	us
Gemini	
Virgo _	
Parma	
Orso _	
Libra _	
Taurus	






Salerno

COLLECTION OF FOILED DOORS









Salerno





CONSTRUCTION

1 the frame is made of an MDF board 1

2 (STANDARD) "honeycomb" filling

3 (OPTIONAL) tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

3

door without a keyhole	no extra charge
• door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ige unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
• automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

DEDICATED DOOR FRAMES


[0B3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129


GLASS



Norma Decor

COLLECTION OF FOILED DOORS











CONSTRUCTION

1 the frame is made of an MDF board 1

2 (STANDARD) "honeycomb" filling

(OPTIONAL)

tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

• width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
• door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ige unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"-"90"	
automatic bottom door seal, widths "100"	
aluminium threshold, widths "60"-"90"	
aluminium threshold, widths "100"	

• ventilation grid

Additional information: equipment and accessories

GLASS

the glossy side of glass is on the hinge side

P. 133–137



DEDICATED DOOR FRAMES

[0B3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

PORTHOLE in NORMA DECOR 6:

available in silver and black colour with the possibility of using a transparent or satin glass pane (option included in the price of the door leaf)

Torino

COLLECTION OF FOILED DOORS









CONSTRUCTION

1 the frame is made of an MDF board

2 (STANDARD) "honeycomb" filling

3 (OPTIONAL) tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

4

width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
• door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hi	nge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
• double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"-"100"	
• aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

• lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

 screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

DEDICATED DOOR FRAMES

 [0B3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS

the glossy side of glass is on the hinge side




chinchilla

no extra charge

Merano

COLLECTION OF FOILED DOORS



DOOR LEAVES OPTIONS



THE DOOR LEAF IS ALSO AVAILABLE IN A REBATED OPTION WITH A SHARP EDGE AND A NON-REBATED OPTION—INFO. P. 102





CONSTRUCTION

1 the frame is made of an MDF board

2 (STANDARD) "honeycomb" filling

3 (OPTIONAL) tubular chipboard filling

4 frame with filling is covered with HDF

boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
• door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hir	nge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"–"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

• lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

 screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

DEDICATED DOOR FRAMES

 [0B3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

satinato

GLASS


no extra charge



Rebated Lido 14 in B134



DOOR LEAVES OPTIONS



THE DOOR LEAF IS ALSO AVAILABLE IN A REBATED OPTION WITH A SHARP EDGE AND A NON-REBATED OPTION—INFO. P. 94, 106





2

CONSTRUCTION

1 the frame is made of an MDF board 2 (STANDARD)

2 (STANDARD) tubular chipboard filling

- frame with filling is covered with HDF boards on both sides
- door leaf covered with ENDURO foil or ECO-VENEERALU strip—8 mm
 - side edges and upper edge are foiled
 - rounded vertical edges of door leaves (more info on p. 122)
 - double door leaves have a rebate and a counter-rebate (drawing on p. 122)

1

4

• width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge	
door width "100"		
• additional hinge for the door in sizes "60"-"80"		
caps for hinges (chrome, satin chrome, golden, black)—set for 1 hinge unit		
ventilation undercut		
PVC ventilation sleeves		
• metal ventilation sleeves, round (chrome, golden)		
metal ventilation sleeves, square (chrome, nickel)		
door made in a non-rebated version for sliding systems		
double door		
• cylinder lock insert 31/36		
tubular chipboard filling	standard	
automatic bottom door seal, widths "60"-"100"		
• aluminium threshold, widths "60""100"		
Additional information: equipment and accessories	P. 133–137	

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"


DEDICATED DOOR FRAMES

[0B3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

Dolce



DOOR LEAVES OPTIONS



THE DOOR LEAF IS ALSO AVAILABLE IN A REBATED OPTION WITH A SHARP EDGE AND A NON-REBATED OPTION—INFO. P. 96





3



CONSTRUCTION

1 the frame is made of an MDF board

(**STANDARD**) "honeycomb" filling

3 (OPTIONAL) tubular chipboard filling

- frame with filling is covered with HDF
- 4 boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
• door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ige unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

DEDICATED DOOR FRAMES

 [0B3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129


GLASS



Strada

COLLECTION OF FOILED DOORS









3

CONSTRUCTION

1 the frame is made of an MDF board 1

2 (STANDARD) "honeycomb" filling

(OPTIONAL)

tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
• door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	nge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"-"100"	
• aluminium threshold, widths "60"–"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

DEDICATED DOOR FRAMES

 [0B3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129


GLASS



Sagittarius

COLLECTION OF FOILED DOORS









CONSTRUCTION

1 the frame is made of an MDF board 1

(STANDARD) "honeycomb" filling

(OPTIONAL)

tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
• door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hir	nge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

DEDICATED DOOR FRAMES


[0B3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129


GLASS



Gemini

COLLECTION OF FOILED DOORS











CONSTRUCTION

1 the frame is made of an MDF board 1 (STANDARD)

2 (STANDARD) "honeycomb" filling

3 (OPTIONAL) tubular chipboard filling

- frame with filling is covered with HDF
- 4 boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

3

door without a keyhole	no extra charge
door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ige unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60""100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

DEDICATED DOOR FRAMES

 [0B3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS






COLLECTION OF FOILED DOORS

1 WATCH THE ASSEMBLY VIDEOS ON OUR YOUTUBE CHANNEL

DOOR LEAVES OPTIONS



THE DOOR LEAF IS ALSO AVAILABLE IN A REBATED OPTION WITH A SHARP EDGE AND A NON-REBATED OPTION—INFO. P. 98







CONSTRUCTION

1 the frame is made of an MDF board 1 (STANDARD)

2 (STANDARD) "honeycomb" filling

3 (OPTIONAL) tubular chipboard filling

4 frame with filling is covered with HDF

boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

3

door without a keyhole	no extra charge
• door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ige unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

• lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

 screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	Р. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129


GLASS



Parma

COLLECTION OF FOILED DOORS











3



CONSTRUCTION

1 the frame is made of an MDF board 1 (STANDARD)

2 (STANDARD) "honeycomb" filling

3 (OPTIONAL) tubular chipboard filling

- frame with filling is covered with HDF
- 4 boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
• door width "100"	
• additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

• lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

 screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	Р. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS




Orso

COLLECTION OF FOILED DOORS



DOOR LEAVES OPTIONS



THE DOOR LEAF IS ALSO AVAILABLE IN A REBATED OPTION WITH A SHARP EDGE AND A NON-REBATED OPTION—INFO. P. 100





CONSTRUCTION

1 the frame is made of an MDF board

2 (STANDARD) "honeycomb" filling

3 (OPTIONAL) tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

door without a keyhole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ge unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
• automatic bottom door seal, widths "60"-"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

- lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

DEDICATED DOOR FRAMES

 [0B3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS




the glossy side of glass is on the hinge side

83

Libra and Taurus

COLLECTION OF FOILED DOORS









TAURUS DOOR LEAVES ARE AVAILABLE ONLY IN CHESTNUT B288

CONSTRUCTION

1 the frame is made of an MDF board

2 (STANDARD) "honeycomb" filling

(OPTIONAL)

tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil or ECO-VENEER

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

ADDITIONAL OPTIONS

3

door without a keyhole	no extra charge
door width "100"	
additional hinge for the door in sizes "60"-"80"	
• caps for hinges (chrome, satin chrome, golden, black)—set for 1 hin	ige unit
ventilation undercut	
PVC ventilation sleeves	
metal ventilation sleeves, round (chrome, golden)	
metal ventilation sleeves, square (chrome, nickel)	
door made in a non-rebated version for sliding systems	
double door	
cylinder lock insert 31/36	
tubular chipboard filling	
automatic bottom door seal, widths "60"–"100"	
aluminium threshold, widths "60"-"100"	
Additional information: equipment and accessories	P. 133–137

STANDARD EQUIPMENT

• lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

 screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	Р. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

GLASS



MODERN AND OPTIMO

LINE

To meet the needs of the market and our most demanding customers, we present six collections of door leaves made in the technology of sharp edge veneering (90°)—**CUT EDGE**.

The **MODERN LINE** collection is available in selected, solid veneers from the standard offer, thanks to which the door can be matched to the interior dedicated to it.

OPTIMO LINE, in addition to the new, unique colours, also offers the possibility of using the edge of the door leaf in a different colour.






New

Belgatto

MODERN LINE COLLECTION



DOOR LEAVES OPTIONS



DECORS





Belgatto door leaves may also be made in a non-rebated version (see additional options table)



3

CONSTRUCTION

1 the frame is made of an MDF board 1 (STANDARD)

2 (STANDARD) "honeycomb" filling

3 (OPTIONAL) tubular chipboard filling

- 4 frame with filling is covered with HDF boards on both sides
- 5 door leaf covered with ENDURO foil
- side edges and upper edge are foiled
- edge band in the colour of the door leaf (STANDARD) or black (OPTION)
- cut edges (90°) of door leaf (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

- width of single doors: "60"-"100" / width of double doors: "120"-"200"
- black milling—"U" with a width of 8 mm

STANDARD EQUIPMENT

non-rebated

rebated	٠	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
reba	•	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome


DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[OR57] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

• (door without a keyhole	no extra charge	
• (door width "100"		
• (door made in non-rebated version		
• (door made in a non-rebated version for sliding systems		
• (double door (selected models)		
tubular chipboard filling			
• ;	automatic bottom door seal, widths "60"–"100"		
aluminium threshold, widths: "60"-"100"			
	cylinder lock insert 31/36		
rebated	• additional hinge for the door in sizes "60"-"80"		
	caps for hinges (chrome, satin chrome, golden, black)—set for	r 1 hinge unit	
10n-rebated	• additional hinge—included in a door frame		
non-re	cylinder lock insert 31/31		
• 1	reinforcement for self-closer		
ventilation undercut			
black edge band of the door leaf (rebated and non-rebated)			
Additional information: equipment and accessories P. 133–137			





DOOR LEAVES OPTIONS










Decorato door leaves may also be made in a non-rebated version (see additional options table)



3

CONSTRUCTION

1 the frame is made of an MDF board (STANDARD)

2 "honeycomb" filling

(OPTIONAL) tubular chipboard filling

- frame with filling is covered with HDF boards 4 on both sides
- 5 door leaf covered with ENDURO foil
- side edges and upper edge are foiled
- . edge band in the colour of the door leaf (STANDARD) or black (OPTION)
- cut edges (90°) of door leaf (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122) •

5

- width of single doors: "60"-"100" / width of double doors: "120"-"200" •
- black milling—"V" with a width of 3 mm

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert	
	 screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100" 	
	non-rebated	 magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
	-LOU	 hidden binges with a 3D regulation in the colour satin chrome

hidden hinges with a 3D regulation in the colour satin chrome .

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS


door without a keyhole no extra char			
door width "100"			
• (door made in non-rebated version		
• (door made in a non-rebated version for sliding systems		
• (double door (selected models)		
tubular chipboard filling			
• ;	automatic bottom door seal, widths "60"-"100"		
aluminium threshold, widths: "60"-"100"			
	cylinder lock insert 31/36		
rebated	• additional hinge for the door in sizes "60"-"80"		
	• caps for hinges (chrome, satin chrome, golden, black)—set for	or 1 hinge unit	
bated	• additional hinge—included in a door frame		
non-rebated	cylinder lock insert 31/31		
reinforcement for self-closer			
ventilation undercut			
black edge band of the door leaf (rebated and non-rebated)			
Additional information: equipment and accessories P. 133–137			



Norma Decor

MODERN LINE COLLECTION











CONSTRUCTION

1 the frame is made of an MDF board

2 (STANDARD) "honeycomb" filling

(OPTIONAL) tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil

- side edges and upper edge are foiled
- edge band in the colour of the door leaf
- cut edges (90°) of door leaf (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

• width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

non-rebated

ited	·	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
rebated	•	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"

- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome


DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[OR58] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[OR57] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

•	door without a keyhole	no extra charge
•	door width "100"	
•	door made in a non-rebated version for sliding systems	
•	double door	
•	ubular chipboard filling	
•	automatic bottom door seal, widths "60"—"100"	
•	aluminium threshold, widths "60"–"100"	
	• additional hinge for the door in sizes "60"-"80"	
ebated	cylinder lock insert 31/36	
-	• caps for hinges (chrome, satin chrome, golden, black)—se	et for 1 hinge unit
non-rebated	• additional hinge for the non-rebated door—included in a	door frame
non-re	cylinder lock insert 31/31	
•	einforcement for self-closer	
•	ventilation undercut	
•	PVC ventilation sleeves	
•	netal ventilation sleeves, round (chrome, golden)	
•	netal ventilation sleeves, square (chrome, nickel)	
•	ventilation grid	
Add	litional information: equipment and accessories	P. 133–137









CONSTRUCTION

the frame is made of an MDF board(STANDARD)

2 (STANDARD) tubular chipboard filling

frame with filling is covered with HDF boards on both sides

4 door leaf covered with ENDURO foil

- side edges and upper edge are foiled
- edge band in the colour of door leaf
- ALU strip—8 mm

non-rebated

- cut edges (90°) of door leaf (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

1

4

• width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

	•	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
rebated		
rebi		screw-in pivot hinges 13.5/9 (white zinc)-2 pcs for door leaves in

- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES


• [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

door without a keyhole no extra charge		
door width "100"		
• (door made in a non-rebated version for sliding systems	
• (double door	
• t	ubular chipboard filling	standard
• ā	automatic bottom door seal, widths "60"–"100"	
aluminium threshold, widths "60"–"100"		
	• cylinder lock insert 31/36	
ebated	• additional hinge for the door in sizes "60"-"80"	
	caps for hinges (chrome, satin chrome, golden, black)—set for	r 1 hinge unit
on-rebated	additional hinge—included in a door frame	
non-re	cylinder lock insert 31/31	
• r	einforcement for self-closer	
ventilation undercut		
PVC ventilation sleeves		
metal ventilation sleeves, round (chrome, golden)		
metal ventilation sleeves, square (chrome, nickel)		
Additional information: equipment and accessories P. 133–137		

Dolce











3

CONSTRUCTION

1 the frame is made of an MDF board

(STANDARD) "honeycomb" filling

2

non-rebated

3 (OPTIONAL) tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil

- side edges and upper edge are foiled
- edge band in the colour of the door leaf
- cut edges (90°) of door leaf (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

• width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

_	•	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
rebated		
2		scrow in pivot hingos 12 5/0 (white zinc) 2 pcs for door logy os in

- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[OR57] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

Dolce 3

	toor without a kowholo		
	door without a keyhole no extra charge		
• (loor width "100"		
• (loor made in a non-rebated version for sliding systems		
• (double door		
۰t	ubular chipboard filling		
• ā	utomatic bottom door seal, widths "60"–"100"		
• ā	luminium threshold, widths "60"–"100"		
	cylinder lock insert 31/36		
ebated	• additional hinge for the door in sizes "60"-"80"		
	• caps for hinges (chrome, satin chrome, golden, black)—set for	r 1 hinge unit	
non-rebated	additional hinge—included in a door frame		
non-re	cylinder lock insert 31/31		
• r	einforcement for self-closer		
• \	rentilation undercut		
PVC ventilation sleeves			
metal ventilation sleeves, round (chrome, golden)			
metal ventilation sleeves, square (chrome, nickel)			
Add	itional information: equipment and accessories	P. 133–137	

GLASS



the glossy side of glass is on the hinge side


97


Virgo

MODERN LINE COLLECTION









3

CONSTRUCTION

1 the frame is made of an MDF board

2 (STANDARD) "honeycomb" filling

3 (OPTIONAL) tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil

- side edges and upper edge are foiled
- edge band in the colour of the door leaf
- cut edges (90°) of door leaf (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

non-rebated

75	•	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
rebated		scraw in pivot hingas 12.5/0 (white zinc) 2 pcs for door lagues in

- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

door without a keyhole no extra charge			
• (loor made in a non-rebated version for sliding systems		
• (louble door		
۰t	ubular chipboard filling		
• ;	utomatic bottom door seal, widths "60"–"100"		
• 6	luminium threshold, widths "60"–"100"		
	cylinder lock insert 31/36		
rebated	• additional hinge for the door in sizes "60"-"80"		
	• caps for hinges (chrome, satin chrome, golden, black)—set for	r 1 hinge unit	
non-rebated	additional hinge—included in a door frame		
non-re	cylinder lock insert 31/31		
• 1	einforcement for self-closer		
ventilation undercut			
PVC ventilation sleeves			
metal ventilation sleeves, round (chrome, golden)			
• 1	netal ventilation sleeves, square (chrome, nickel)		
Ado	itional information: equipment and accessories	P. 133–137	

GLASS




the glossy side of glass is on the hinge side

99

Orso









CONSTRUCTION

1 the frame is made of an MDF board

2 (STANDARD) "honeycomb" filling

3 (OPTIONAL) tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil

- side edges and upper edge are foiled
- edge band in the colour of the door leaf
- cut edges (90°) of door leaf (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

non-rebated

	•	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
rebated		
5		$r_{\rm crow}$ in pivot binger 12.5 (0 (white zinc) 2 pcc for deer leaves in

- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

	teres the state terms		
• (door without a keyhole no extra charge		
• (door width "100"		
• (door made in a non-rebated version for sliding systems		
• (double door		
• 1	ubular chipboard filling		
• ;	automatic bottom door seal, widths "60"–"100"		
aluminium threshold, widths "60"-"100"			
	cylinder lock insert 31/36		
ebated	• additional hinge for the door in sizes "60"-"80"		
_	• caps for hinges (chrome, satin chrome, golden, black)—set for	r 1 hinge unit	
on-rebated	additional hinge—included in a door frame		
non-re	cylinder lock insert 31/31		
• 1	einforcement for self-closer		
ventilation undercut			
PVC ventilation sleeves			
metal ventilation sleeves, round (chrome, golden)			
metal ventilation sleeves, square (chrome, nickel)			
Additional information: equipment and accessories P. 133–137			


GLASS



Merano









CONSTRUCTION

1 the frame is made of an MDF board

2 (STANDARD) "honeycomb" filling

(OPTIONAL) tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with ENDURO foil

- side edges and upper edge are foiled
- edge band in the colour of the door leaf
- cut edges (90°) of door leaf (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)

5

width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

non-rebated

75	•	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
rebated		scraw in pivot hingos 12.5/0 (white zinc) 2 pcs for door looves in

- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[OR57] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

• (loor without a keyhole	no extra charge	
• (door width "100"		
• (door made in a non-rebated version for sliding systems		
• (double door		
tubular chipboard filling			
automatic bottom door seal, widths "60""100"			
aluminium threshold, widths "60"-"100"			
	cylinder lock insert 31/36		
rebated	• additional hinge for the door in sizes "60"-"80"		
	• caps for hinges (chrome, satin chrome, golden, black)—set for	r 1 hinge unit	
on-rebated	additional hinge—included in a door frame		
non-re	cylinder lock insert 31/31		
• r	einforcement for self-closer		
• \	rentilation undercut		
• F	VC ventilation sleeves		
metal ventilation sleeves, round (chrome, golden)			
• r	netal ventilation sleeves, square (chrome, nickel)		
Adc	itional information: equipment and accessories	P. 133–137	


GLASS



Norma Decor



DOOR LEAVES OPTIONS



DECORS CPL 0.15 MM •••• CPL 0.8 MM •••• B672 CPL 0.15 B728 CPL 0.8 B729 CPL 0.15 B730 CPL 0.8 B687 CPL 0.15 B727 CPL 0.15 B732 CPL 0.8 B736 CPL 0.8 B688 CPL 0.8 B731 CPL 0.15 alpine white diamond grey brown metallie dark brown charleston oa light c ENDURO POLI ···· B733 CPL 0.15 B717 CPL 0.8 B734 CPL 0.15 B735 CPL 0.8 B746 CPL 0.15 B747 CPL 0.15 B726 grey nebraska oał natural hamilton oa pearl grey polar pin

Norma Decor



CONSTRUCTION

1 the frame is made of an MDF board

2 (STANDARD) "honeycomb" filling

(OPTIONAL)

tubular chipboard filling

4 frame with filling is covered with HDF boards on both sides

5 door leaf covered with the CPL 0.15 mm or CPL 0.8 mm foil

- side edges and upper edge are foiled
- edge band in the colour of the door leaf; option for non-rebated doors (see table on page 10). In double non-rebated door leaves, edge band in the colour of the door leaf and silver fittings are standard. However, it is possible to make them with black edge band and fittings as part of a custom order. In this case, please contact our Customer Service.

5

- cut edges (90°) of the door leaf (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated

ebated

-uou

	·	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
--	---	---

- screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
- magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
- hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

Image: Contract of the second seco

ADDITIONAL OPTIONS

3

• (loor without a keyhole	no extra charge	
• (door width "100"—CPL 0.15 mm		
• (door width "100"—CPL 0.8 mm		
• (loor made in a non-rebated version for sliding systems		
• (double door		
• t	ubular chipboard filling		
• ā	utomatic bottom door seal, widths "60"-"100"		
• ā	aluminium threshold, widths: "60"-"100"		
-0	cylinder lock insert 31/36		
ebated	• additional hinge for the door in sizes "60"-"80"		
2	• caps for hinges (chrome, satin chrome, golden, black)—set for	1 hinge unit	
	additional hinge for the non-rebated door—included in a doc	or frame	
B	cylinder lock insert 31/31		
non-rebated	• edge band in the following colours: B726 or B688		
non	• edge band in the colour: B717 (option only for the leaf in B68	7, B688)	
	 a set of: 2 hinges + striking plate + door lock in colours: white, golden, black 	satin chrome,	
• r	reinforcement for self-closer		
ventilation undercut			
PVC ventilation sleeves			
metal ventilation sleeves, round (chrome, golden)			
metal ventilation sleeves, square (chrome, nickel)			
ventilation grid			
Adc	litional information: equipment and accessories	P. 133–137	



PORTHOLE in NORMA DECOR 6: available in silver and black colour with the possibility of using a transparent or satin glass pane (option included in the price of the door leaf)

Lido



DOOR LEAVES OPTIONS



DECORS

CPL 0.15 MM •••• B672 CPL 0.15 B687 CPL 0.15 B727 CPL 0.15 B729 CPL 0.15 B731 CPL 0.15 alpine white dark brown charleston oak diamond grey light concrete brown metallic ENDURO POLI ···· B733 CPL 0.15 B734 CPL 0.15 B746 CPL 0.15 B747 CPL 0.15 B726 natural hamilton oak grey nebraska oak pearl grey polar pine



3

CONSTRUCTION

1 the frame is made of an MDF board 2 (STANDARD)

2 (STANDARD) tubular chipboard filling

- frame with filling is covered with HDF boards on both sides
- door leaf covered with the CPL 0.15 mmside edges and upper edge are foiled
- edge band in the colour of the door leaf; option for non-rebated doors (see table on page 10). In double non-rebated door leaves, edge band in the colour of the door leaf and silver fittings are standard. However, it is possible to make them with black edge band and fittings as part of a custom order. In this case, please contact our Customer Service.

1

4

- ALU strip—8 mm
- cut edges (90°) of the door leaf (more info on p. 122)
- double door leaves have a rebate and a counter-rebate (drawing on p. 122)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	 screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	 magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
	hidden hinges with a 3D regulation in the colour satin chrome

DEDICATED DOOR FRAMES

[0B3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126
[OR57] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 127
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 127
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 128-129

ADDITIONAL OPTIONS

• (door without a keyhole	no extra charge	
door width "100"—CPL 0.15 mm			
• (door made in a non-rebated version for sliding systems		
• (double door		
automatic bottom door seal, widths "60"-"100"			
aluminium threshold, widths: "60"–"100"			
-	cylinder lock insert 31/36		
rebated	• additional hinge for the door in sizes "60""80"		
Ð	• caps for hinges (chrome, satin chrome, golden, black)—set fo	r 1 hinge unit	
	• additional hinge for the non-rebated door—included in a doo	or frame	
p	cylinder lock insert 31/31		
non-rebated	• edge band in the following colours: B726 or B688		
-uou	• edge band in the colour: B717 (option only for the leaf in B68	37)	
	a set of: 2 hinges + striking plate + door lock in colours: white golden, black	, satin chrome,	
• 1	reinforcement for self-closer		
• \	ventilation undercut		
• [PVC ventilation sleeves		
metal ventilation sleeves, round (chrome, golden)			
metal ventilation sleeves, square (chrome, nickel)			
Ado	ditional information: equipment and accessories	P. 133–137	

Amber

COLLECTION OF GLASS DOORS



LOCK COLOURS

Anodized silver [F150]

Stainless steel [F157]

lack





Amber doors are divided into groups due to the types of glass decorations

GROUP I—basic glass (transparent or matte in various shades)

Amber 13—satinato glass	
Amber 14—transparent glass	
Amber 15—transparent glass	

GROUP II—decorated glass (engraving or overprint) Amber 3—overprint on transparent glass Amber 6—overprint on transparent glass Amber 12—engraving on satinato glass

CONSTRUCTION

- tempered glass, 8 mm thick
- the matt side of a glass pane is on the hinge side
- block or adjustable door frame, 2 hinges

DIMENSIONS OF GLASS DOORS (mm)

	"60"	"70"	"80"	"90"
door leaf width	617	717	817	917
door leaf height		(PL) 2027 / 1	975 (CZ/SK)	

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126

ADDITIONAL OPTIONS

• ventilation undercut







Norma Decor and Libra



DOOR LEAVES OPTIONS







CONSTRUCTION

- construction of each half of the folding door consists of a frame made of MDF board or 33 mm thick semifinished coniferous wood glued in layers
- 2 "honeycomb" filling

frame and filling are covered with3 mm thick MDF boards

Folding doors—NORMA DECOR 1

4 door leaf covered with ENDURO foil or ECO-VENEER

• folding doors consist of a folding door and a block or adjustable door frame

1

4

- each half of a door leaf has a rabbet along the vertical edge
- both parts of a door leaf are joined together with hidden hinges
- the door leaf is connected to the floor with a spigot fixed in the holder,
 which is bolted to the floor
- the upper part is connected to the door frame with a spigot fixed in the holder, which is mounted in the rail bolted to the upper element of the door frame
- the sliding mechanism (trolley), mounted on the rail, stabilizes the door leaf when opening and closing
- rounded vertical edges of door leaves (more info on p. 122)
- universal door leaf ready to be mounted on the left or right side
- width of single doors: "60"-"90"

STANDARD EQUIPMENT

- 2 silver round grips in colour satin chrome
- 2 hidden hinges in colour satin chrome

DEDICATED DOOR FRAMES

 [OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) 	P. 125
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 126
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 126





GLASS



the glossy side of glass is on the hinge side

Pocket door sliding system

SLIDING SYSTEMS



The cassette with thickness 100 mm is designed for modular door leaves (eg. Domino, Versano, Tamparo) and standard flat doors.

The cassette with thickness 125 mm is designed for standard foiled door leaves (eg Torino, Strada).

DOOR LEAVES OPTIONS



• key

• WC

STANDARD EQUIPMENT (THE SET INCLUDES)

- construction cassette for the sliding system in sizes "100" or "125"
- set of profiles (door frame), brushes and seals
- set of covering profiles for both sides of the door frame
- grip (chrome, satin, golden or black)

ADDITIONAL OPTIONS

- soft-close hardware for sliding door
- key hook lock or WC hook lock (chrome, satin, golden, black) with a grip suitable for key or WC lock. In case of door leaves equipped with a hook lock, the customer installs the striking plate in the door frame on their own
- tunnel (door frame enlarging element)—price per each 10 mm
- strike plate

112

DIAGRAM OF THE LOCATION OF DOOR FRAME ELEMENTS FOR SLIDING SYSTEM—SINGLE SLIDING SYSTEM




DIAGRAM OF THE LOCATION OF DOOR FRAME ELEMENTS FOR SLIDING SYSTEM—DOUBLE SLIDING SYSTEM






DIAGRAM OF THE LOCATION OF DOOR FRAME ENLARGING ELEMENTS FOR THE POCKET DOOR SLIDING SYSTEM





arip with a folding key and a thimble

grip with a grip and a WC knob and thimble a thimble

strike plate

door seal

profiles and architraves

brush



(B)

В

640

740

840

940

1040

Α

1290

1490

1690

1890

2090

wall

thickness

100 - 125

DOOR LEAF DIMENSIONS (mm)

width

644

744

844

944

1044

height


2040 (PL)

1988 (CZ-SK)

soft-close hardware for sliding door

SLIDING SYSTEMS

Wall-mounted sliding system





DOOR LEAVES OPTIONS



STANDARD EQUIPMENT (THE SET INCLUDES)

- rail cover in the door leaf decor—installed on ALU strip (two types, depending on the width of the masking angle architrave used in the door frame—60 mm or 80 mm)
- rail—installed on ALU strip
- grip—a set for both sides of the door leaf, and a thimble—1 piece (chrome, satin, golden, black)

ADDITIONAL OPTIONS AT EXTRA CHARGE


• soft-close hardware for sliding door


	ENDURO / PLUS / 3D
bumper	ECO-VENEER / ENDURO POLI
	• CPL 0,15 mm
• key hook lock or WC hook lock (chrome, satin,	• key
golden, black) with a grip suitable for key or WC lock	• WC

DIMENSIONS OF THE DOOR LEAF AND THE DOOR FRAME FOR THE WALL-MOUNTED SLIDING SYSTEM

			C	door frame	e for single	door (mn	ר)	d	door frame for double door (mm) – ATTENTION: CHANGE OF DIMENSIONS						٨S	
			"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150	"160"	"170"	"180"	"190"	"200"
s1	door leaf width		644	744	844	944	1044	1304	1404	1504	1604	1704	1804	1904	2004	2104
s2	width of the wall openi	ing*	674	774	874	974	1074	1310	1410	1510	1610	1710	1810	1910	2010	2110
s3	outer width of the doo	r frame	644	744	844	944	1044	1280	1380	1480	1580	1680	1780	1880	1980	2080
s4	internal width of the do	oor frame	600	700	800	900	1000	1236	1336	1436	1536	1636	1736	1836	1936	2036
_	width of the door	60 mm [ORS3]	744	844	944	1044	1144	1380	1480	1580	1680	1780	1880	1980	2080	2180
s5	frame with architraves	80 mm [ORS9]	784	884	984	1084	1184	1420	1520	1620	1720	1820	1920	2020	2120	2220
h1	door leaf height							2	1040 (PL) / 1	988 (CZ-SK	.)					
h2	height of the wall oper	ning						2	1062 (PL) / 2	2008 (CZ-SK	.)					
h3	outer height of the doo	or frame						2	.047 (PL) / 1	993 (CZ-SK	.)					
h4	internal height of the d	loor frame*	2025 (PL) / 1971 (CZ-SK)													
	height of the door	60 mm [ORS3]						2	1097 (PL) / 2	2043 (CZ-SK	()					
h5	frame with architraves	80 mm [ORS9]						2	117 (PL) / 2	2063 (CZ-SK	.)					

*Dimensions of the wall opening for the version without a door frame should be identical to the internal width of the door frame.





AVAILABLE DOOR FRAMES

[ORS3] adjustable door frame with a flat angle architrave 60 mm-wide the set includes: a door frame and a bumper with milling and striking plate

[ORS9] adjustable door frame with a flat angle architrave 80 mm-wide the set includes: a door frame and a bumper with milling and striking plate

CLASSIFICATION OF RAILS AND RAIL COVERS DEPENDING ON THE WIDTH OF THE SLIDING SYSTEM

door leaf	length of rail cover	number of rail cover elements	number of rails and angle architraves	length of rail cover	length of rail cover	number of rail cover elements	number of rails and angle architraves		
"60"	1350 mm			"70" + "70" or "60" + "80"	3000 mm				
"70"	1550 mm		1 rail and angle archi-	"70" + "80" or "60" + "90"	3200 mm		2 rails and angle architraves 200 cm-long		
"80"	1750 mm	1 element	trave 200 cm-long	"80" + "80" or "70" + "90" or "60" + "100"	3400 mm				
"90"	1950 mm			"80" + "90" or "70" + "100"	3600 mm				
"100"	2150 mm			"90" + "90" or "80" + "100"	3800 mm				
"60" + "60"	2600 mm		2 rails and angle archi- traves 200 cm-long	"90" + "100"	4000 mm				
"60" + "70"	2800 mm	2 elements	traves 200 ern long	"100" + "100"	4200 mm		3 rails and angle architraves 200 cm-long		









Rail cover dimensions: **A**—91.5 mm [ORS3] or 111.5 mm [ORS9] **B**—92 mm





grip with a folding grip with a WC knob key and a thimble and a thimble

a thimble

grip and

rail cover

B

bumper

soft-close hardware for sliding door

115

Egida



DOOR LEAVES OPTIONS



EGIDA door has burglary resistance (RC 2) only when purchased with a complete dedicated set, which includes a door leaf with a door frame, a threshold, a handle with an escutcheon in min. class 2, and a cylinder insert in min. class 4.





3

CONSTRUCTION

- 1 frame is made of plywood
- 2 filling element: tubular chipboard
- 3 frame with filling is covered with HDF boards on both sides

1

4

2

- 4 door leaf covered with ENDURO foil or ECO-VENEER
- door leaf thickness: 40 mm
 cut edges (90°) of the door leaf (more info.)
- cut edges (90°) of the door leaf (more info on p. 122)
- width of single doors: "80"-"100"

STANDARD EQUIPMENT

- multipoint strip lock with 3 security bolts
- 3 reinforced hinges + 3 anti-burglary pins
- acoustic insulation Rw = 29 dB (acoustic insulation class Rw = 27 dB)
- ANTI-BURGLARY resistance class RC2
- fixed aluminium threshold



ADDITIONAL OPTIONS

- handle + QUEBECK shield—anti-burglary resistance class II (color INOX and TITAN)
- handle + ROYAL shield—anti-burglary resistance class III (color INOX)
- set of WILKA cylinder lock inserts (insert + insert with a knob), ANTI-BURGLARY resistance class 2, 30 x 40 mm, 6 keys

• panoramic viewfinder

• automatic door bottom seal for doors "80"-"100"

NOTE: automatic bottom door seal is not applicable for doors with fixed threshold, therefore it is not included in the set.


DIMENSIONS

		wooden door frame [KOBA] (mm)				tal door fra (OBM] (mr		
		"80"	"90"	"100"	"80"	"90"	"100"	
s1	door leaf width	844	944	1044	844	944	1044	
s2	width of the wall opening	920	1020	1120	890	990	1090	
s3	outer width of the door frame	890	990	1090	880	980	1080	
s4	internal width of the door frame	802	902	1002	800	900	1000	
s5	width of the door frame with architraves				906	1006	1106	
h1	door leaf height	2040 (F	°L) / 1988 (CZ-SK)	2040 (PL)			
h2	internal height of the door frame	2084 (F	PL) / 2030 (CZ-SK)	2070 (PL)			
h3	outer height of the door frame	2069 (PL) / 2015 (CZ-SK)				2064 (PL)		
h4	internal height of the door frame	2025 (PL) / 1971 (CZ-SK)			2024 (PL)			
h5	height of the door frame with architraves		-			2077 (PL)		

DEDICATED DOOR FRAMES

[KOBA]—block door frame: 90 x 44 mm made of plywood covered with MDF board—width "80"–"100"

[KOBM]—metal door frame in RAL color: available as standard in brown color (8017) other colors—honey (8003), white (9010), beige (1001) and grey (7047)*—width "80"-"100"



Ignis fire doors are flush, rebated, and single door leaves with fire resistance **El**₂**30**. The door frame is made of non-flammable chipboard. Door leaf and door frame made of nonflammable chipboard can be installed in walls with fire resistance class **El**₂**30** according to **PN-EN 13501-2:2016-07** and min. density 575 kg/m³, in case of masonry walls made of ceramic or silicate bricks with a minimum thickness of 115 mm, concrete or reinforced concrete walls with a minimum thickness of 115 mm, and walls made from blocks or cellular concrete blocks with a minimum thickness of 115 mm.

DOOR LEAVES OPTIONS









FILLING Mineral wool

CONSTRUCTION

1 frame: laminated pinewood

2 filling: mineral wool

> frame with filling is covered with HDF boards on both sides

4 door leaf covered with ENDURO foil or ECO-VENEER • door leaf thickness: 40 mm

- cut edges (90°) of the door leaf (more info on p. 122)
- width of single doors: "60"-"100"

STANDARD EQUIPMENT

 set of intumescent seals latch-bolt lock • 3 screw-in pivot hinges

2

Fire doors should be a subject of technical inspections and maintenance operations in accordance with the rules set out in the applicable standards and regulations on fire-resistance doors. Technical and maintenance inspections should be carried out at least once a year.

ADDITIONAL OPTIONS

• door leaf width "100"

DIMENSIONS

		"60"	"70"	"80"	"90"	"100"
s1	door leaf width	644	744	844	944	1044
s2	width of the wall opening	696	796	896	996	1096
s3	outer width of the door frame	666	766	866	966	1066
s4	internal width of the door frame	600	700	800	900	1000
s5	width of the door frame with architraves	744	844	944	1044	1144
h1	door leaf height		2042 (P	L) / 1987	(CZ-SK)	
h2	internal height of the door frame		2062 (P	L) / 2007	(CZ-SK)	
h3	outer height of the door frame		2047 (P	L) / 1992	(CZ-SK)	
h4	internal height of the door frame		2025 (P	L) / 1970	(CZ-SK)	
h5	height of the door frame with architraves		2097 (P	L) / 2042	(CZ-SK)	

ONLY SOLD TOGETHER WITH

- cylinder lock insert
- self-closer
- UNO door handle






DEDICATED DOOR FRAMES

IGNIS LEAVES ARE SOLD ONLY WITH THE ORS1/E WOODEN DOOR FRAME—adjustable, made of non-flammable chipboard

	symbol	В	С	D	E	F	G	н	I.
\	wall thickness	100-119	120-139	140-159	160-179	180-199	200-219	220-239	240-259
	symbol	J	К	L	М	N	0		P



wooden interior entrance doors of HALSPAN system



APPLICATION:

Halspan system doors are intended for use in residential and public buildings as interior doors to the extent resulting from their performance characteristics set out in point 3 of the National Technical Assessment ITB-KOT-2018/0407, 1st edition. The doors have a **NATIONAL CERTIFICATE OF STABLE PERFORMANCE No. AC 158-UWB-W1355.**


Acoustic insulation index for GUARDIA El_30 i El_60:

Rw=32 db—Single door leaves El₂30 and El₂60 Rw=32 db—Double door leaf El₁60 Rw=27 db—Double door leaf El₂30

Fire resistance: El,30 (30 min), El,60 (60 min)



DOOR LEAVES OPTIONS





Fire doors should be a subject of technical inspections and maintenance operations in accordance with the rules set out in the applicable standards and regulations on fire-resistance doors. Technical and maintenance inspections should be carried out at least once a year.

The doorset is supplied with:

- a cylinder insert according to requirements of PN-EN 1303: 2015-07,
 a self-closer according to requirements of PN-EN 1154: 1999 / AC: 2010P,
- a complete door handle according to requirements of PN-FN 1906: 2012.
- a closing sequence controller according to requirements of PN-EN 1158: 1999 / AC: 2006P (for double doors only).

1

4

NOTE: the seller is obligated to sell technical doors equipped with above elements (at extra charge)

2



automatic bottom door seal

CONSTRUCTION

- 1 coating: finger joint pinewood
- 2 filling: fireproof chipboard

frame with filling is covered with HDF boards on both sides

4 door leaf covered with ENDURO foil or ECO-VENEER

door leaf thickness: El, 30—50 mm / El, 60—60 mm

- cut edges (90°) of the door leaf (more info on p. 122)
- width of single doors: "70"-"100"
- width of double doors: "140"-"200"

STANDARD EQUIPMENT

- cylinder lock insert
- 4 hinges with regulation
- intumescent seals
- automatic bottom door seal

NOTE: automatic bottom door seal is not applicable for doors with fixed threshold

ADDITIONAL OPTIONS

• viewfinder

3

- smoke protection
- set of 8 mounting screws with expansion sleeves in sizes 10/152 for brick walls

ONLY SOLD TOGETHER WITH

- cylinder lock
- UNO door handle
- door closer meeting the requirements of PN-EN 1154:1999/AC:2010P (single door)
- closing sequence controller (double door)
- TS5000 door closer meeting the requirements of PN-EN 1154:1999/AC:2010P (single door with smoke protection)

NOTE: the seller's obligation is to sell technical doors equipped with the above elements

DIMENSIONS

			single	door (mm)				d	ouble door* (mm)		
		"70"	"80"	"90" **	"100"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width	748	848	964	1048	1487	1587	1687	1787	1887	1987	2087
s2	width of the wall opening	856	956	1072	1156	1595	1695	1795	1895	1995	2095	2195
s3	outer width of the door frame	826	926	1042	1126	1565	1665	1765	1865	1965	2065	2165
s4	internal width of the door frame	706	806	922	1006	1445	1545	1645	1745	1845	1945	2045
h1	door leaf height		ź	2040		2040						
h2	internal height of the door frame		ź	2100		2100						
h3	outer height of the door frame		2084			2084						
h4	internal height of the door frame		2	2024					2024			

* Internal width of the door frame for double door 90+90 after opening the active door leaf at an angle of 90° is at least 900 mm, so the passive door leaf is narrower. The door set is asymmetric regarding widths of both door leaves.

** Internal width of the door frame after opening the door leaf at an angle of 90° is at least 900 mm

DEDICATED DOOR FRAME



[KOBP] block door frame 124 x 60 mm made of finger-joint pinewood

standard—no extra charge

ADDITIONAL OPTIONS AT EXTRA CHARGE FOR BLOCK DOOR FRAME

• covering profile (architrave LO1)—"70"-"100"


• quadrant LC1—"70"-"100"

angle architrave

• enlarging element—100 mm, 200 mm, 300 mm


Technical information

DIMENSIONS OF REBATED, NON-REBATED AND SLIDING DOORS



A REBATE AND A COUNTER-REBATE IN DOUBLE DOOR LEAVES

B



ROUNDED VERTICAL AND UPPER EDGES IN DOOR LEAVES

DOORS	SM	/ING	SLIDING SYSTEMS	EDGE FROM THE CONTACT					
DOORS	REBATED	NON-REBATED	SLIDING STSTEMS	SIDE OF DOUBLE DOOR					
MODULAR DOORS	YES	YES	YES	YES					
FLAT DOORS	YES		NO	NO					
FLAT DOORS (MODERN AND OPTIMO LINE)	NO	NO	NO	NO					
FOLDING DOORS	YES*								
EGIDA	NO								
GUARDIA	NO			NO					
IGNIS	NO								
* OUTER VERTICAL EDGES ONLY.									

* OUTER VERTICAL EDGES ONLY.

VENTILATION

According to the norm, the door to the bathroom, shower, and separate WC should open outwards, have a passage width of at least 0.8 m and height of 2 m, and have ventilation holes for the air supply in the bottom of the door with total ventilation area of at least 0.022 m^2 . The total ventilation area is the sum of the gap under the door (standard 7 mm) and additional solutions that increase the total net ventilation area such as ventilation sleeves, ventilation undercut, and ventilation grid. The use of a ventilation grid ensures the correct ventilation area for all door widths, while using the sleeve and/or undercut the increased gap between the door and the floor should be used to meet the required regulations. If the regulations mentioned above must be obliged, the clients must trim the door on their own.



(visualization for door leaf width "80")



VENTILATION SLEEVES (visualization for door leaf width "80")



VENTILATION GRID (visualization for door leaf width "80")



RECUPERATION (visualization for door leaf width "80")



METAL VENTILATION SLEEVES, SQUARE (chrome, nickel)



METAL VENTILATION SLEEVES, ROUND (chrome, golden)





(Norma Decor, variety of colours)

door width	door leaf with number of ventilation sleeves		door leaf with PVC ventilation sleeves for foiled doors	door leaf with PVC ventilation sleeves for modular doors	total ventilation area: ventilation undercut and the gap under	total ventilation area: ventilation grid nd the gap under
	SIEEVES	total ventilation area	: ventilation sleeves and the gap	o under the door (7 mm) [m2]	the door (7 mm) [m ²]	the door (7 mm) [m ²]
"60"	3	0.0069	0.0062	0.0056	0.00835	
"70"	4	0.0085	0.0075	0.0067	0.01085	
"80"	5	0.0101	0.0089	0.0079	0.01335	> 0.022
"90"	6	0.0117	0.0103	0.0090	0.01585	
"100"	6	0.0124	0.0110	0.0097	0.01835	

NOTE: THE D'ARTAGNAN DOOR LEAVES CANNOT BE USED WITH VENTILATION SLEEVES, UNDERCUTS AND GRIDS. THE SLIDING LEAVES MEET THE VENTILATION REQUIREMENT DUE TO THE SYSTEM CONSTRUCTION. INVADO DOES NOT MAKE SEVERAL VENTILATION SOLUTIONS AT THE SAME TIME.

GUIDELINES FOR BUILDINGS EQUIPPED WITH A RECUPERATION SYSTEM

To ensure adequate airflow from the living areas to the corridor, sanitary, and auxiliary rooms, it is recommended that all internal doors should have a gap at the bottom. The gap area in doors in living and auxiliary rooms should be at least 80 cm² (INVADO doors with an undercut fully meet this requirement). The size of the ventilation gap in doors in sanitary rooms should be 200 cm².

DOOR FRAMES



www.invado.pl

Block door frame











CONSTRUCTION


- MDF board
- foiling—all decors available in the INVADO offer
- cross-section: 90 x 44 mm

DOOR FRAME FOR DOOR LEAVES IN WIDTH

- width of single doors "60" to "100"
- width of double doors "120" to "200"

OPTIONS AT EXTRA CHARGE FOR BLOCK DOOR FRAMES


- flat architrave LO1 60 x 10 mm "60"-"100"
- flat architrave LO7 80 x 16 mm "60"-"100"
- quadrant LC1
- door frames with sidelights and transoms (without glass) with circumference up to 5 l.m
- door frames for double doors
- additional hinge in door frame "60"-"80"



APPLICATION OF QUADRANT LC2 AND

ARCHITRAVE LO1, AND THEIR COVERING SURFACES

COVERINGTRIMS(LO1)ANDQUADRANT(LC1)CAN BE APPLIED TO A BLOCKDOORFRAME FORDOORLEAVESIN WIDTHS"60"-""90".INCASEOFDOORLEAVES IN WIDTH "100", YOUHAVE TOORDERDUBLECOVERING TRIM ORDOUBLEBLE QUADRANT (LC2).



DIMENSIONS

		width of single doors (mm)						width of double doors (mm)—ATTENTION: CHANGE OF DIMENSIONS							
		"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width	644	744	844	944	1044	1280	1380	1480	1580	1680	1780	1880	1980	2080
s2	width of the wall opening	718	818	918	1018	1118	1354	1454	1554	1654	1754	1854	1954	2054	2154
s3	outer width of the door frame	688	788	888	988	1088	1324	1424	1524	1624	1724	1824	1924	2024	2124
s4	internal width of the door frame	600	700	800	900	1000	1236	1336	1436	1536	1636	1736	1836	1936	2036
h1	door leaf height						20	40 (PL) / 1	987 (CZ-S	SK)					
h2	height of the wall opening						20	84 (PL) / 2	2029 (CZ-S	SK)					
h3	outer height of the door frame 2069 (PL) / 2014 (CZ-SK)														
h4	internal height of the door frame 2025 (PL) / 1970 (CZ-SK)														

Adjustable door frame









www.invado.pl

CONSTRUCTION

- MDF board
- · foiling—all decors available in the INVADO offer
- the standard adjustable door frame consists of a central element plus 2 sets of angle architraves joined at 45°. A standard angle architrave consists of a flat architrave 60 mm-wide and a "tongue" 30 mm-long. It is possible to separately order a set of angle architraves 80 mm-wide and/or a set of angle architraves 80 mm-wide with a "tongue" 50 mm-long (see table of options at extra charge).

DOOR FRAME FOR DOOR LEAVES IN WIDTH

- width of single doors "60" to "100"
- width of double doors "120" to "200"

OPTIONS AT EXTRA CHARGE FOR BLOCK DOOR FRAMES

- door frames with sidelights and transoms (without glass) with circumference up to 5 l.m
- door frames for double doors •
- additional hinge in door frame "60"-"80" •
- standard angle architrave (a "tongue" 30 mm-long, an architrave 60 or 80 mm-wide) •
- angle architrave with longer "tongue" (a "tongue" 50 mm-long, an architrave 60 or • 80 mm-wide)
- wall framing ("blind door frame") .

DIMENSIONS








The adjustable door frame is made in dimensions adjustable to the wall thickness in steps of 20 mm. The minimum wall thickness is 75 mm

NOTE: due to special mills, there is a possibility to trim the frame and reduce the wall thickness coverage by 15 mm. Door frame for wall thickness greater than 360 mm consists of at least two connected components.



width of double doors (mm)—ATTENTION: CHANGE OF DIMENSIONS

		width of single doors (mm)							width of double doors (mm)—ATTENTION: CHANGE OF DIMENSIONS							
			"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width		644	744	844	944	1044	1280	1380	1480	1580	1680	1780	1880	1980	2080
s2	width of the wall of	pening	674	774	874	974	1074	1310	1410	1510	1610	1710	1810	1910	2010	2110
s3	outer width of the o	door frame	644	744	844	944	1044	1280	1380	1480	1580	1680	1780	1880	1980	2080
s4	internal width of th	e door frame	600	700	800	900	1000	1236	1336	1436	1536	1636	1736	1836	1936	2036
_	width of the	60 mm [ORS1]	744	844	944	1044	1144	1380	1480	1580	1680	1780	1880	1980	2080	2180
s5	door frame with architraves	80 mm [ORS8]	784	884	984	1084	1184	1420	1520	1620	1720	1820	1920	2020	2120	2220
h1	door leaf height							20	40 (PL) / 1	988 (CZ-S	5K)					
h2	height of wall oper	iing						20	62 (PL) / 2	2008 (CZ-S	5K)					
h3	outer height of the	door frame						20	47 (PL) / 1	1993 (CZ-S	5K)					
h4	internal height of th	ne door frame						20)25 (PL) /	1971 (CZ-9	SK)					
	height of the	60 mm [ORS1]						20	97 (PL) / 2	2043 (CZ-S	5K)					
h5	door frame with architraves	80 mm [ORS8]						21	17 (PL) / 2	2063 (CZ-S	5K)					

Adjustable door frame





ADJUSTABLE DOOR FRAME + ANGLE ARCHITRAVE 80 MM-WIDE



• MDF board

CONSTRUCTION

- foiling—all decors available in the INVADO offer
- the standard adjustable door frame consists of a central element plus 2 sets of angle architraves joined at 45°. A standard angle architrave consists of a flat architrave 60 mm-wide and a "tongue" 30 mm-long. It is possible to separately order a set of angle architraves 80 mm-wide and/or a set of angle architraves 80 mm-wide with a "tongue" 50 mm-long (see table of options at extra charge).

DOOR FRAME FOR DOOR LEAVES IN WIDTH

- width of single doors "60" to "100"
- width of double doors "120" to "200"

OPTIONS AT EXTRA CHARGE FOR BLOCK DOOR FRAMES

- · door frames with sidelights and transoms (without glass) with circumference up to 5 l.m
- door frames for double doors
- additional hinge in door frame
- standard angle architrave (a "tongue" 30 mm-long, an architrave 60 or 80 mm-wide)
- angle architrave with longer "tongue" (a "tongue" 50 mm-long, an architrave 60 or 80 mm-wide)

DIMENSIONS

wall thickness from 360 mm

Door frame for


RANGES OF WALL THICKNESS COVERING






The adjustable door frame is made in dimensions adjustable to the wall thickness in steps of 20 mm. The minimum wall thickness is 75 mm.

NOTE: for wall thickness between 75-85, it is required to use wall frame A(75-94). In this case, the angle architrave should be trimmed where the mills are located—otherwise, the door frame won't be properly aligned with the wall. Door frames for a wall thickness greater than 360 mm consist of at least two connected elements.






	width of single doors (mm)							width of double doors (mm)								
			"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width		618	718	818	918	1018	1239	1339	1439	1539	1664	1739	1839	1939	2039
s2	width of the wall o	pening	674	774	874	974	1074	1294	1394	1494	1594	1694	1794	1894	1994	2094
s3	outer width of the	door frame	644	744	844	944	1044	1264	1364	1464	1564	1664	1764	1864	1964	2064
s4	internal width of th	e door frame	600	700	800	900	1000	1220	1320	1420	1520	1620	1720	1820	1920	2020
-5	width of the door frame with	60 mm [ORS7]	744	844	944	1044	1144	1364	1464	1564	1664	1764	1864	1964	2064	2164
s5	architraves	80 mm [ORS10]	784	884	984	1084	1184	1404	1504	1604	1704	1804	1904	2004	2104	2204
h1	door leaf height							20	27 (PL) / 1	1975 (CZ-S	5К)					
h2	height of wall oper	ning						20	62 (PL) / 2	2008 (CZ-S	5К)					
h3	outer height of the	door frame						20	47 (PL) / 1	1993 (CZ-S	5K)					
h4	internal height of t	he door frame						20	025 (PL) /	1971 (CZ- :	SK)					
	height of the	60 mm [ORS7]						20	97 (PL) / 2	2043 (CZ-S	5K)					
h5	door frame with architraves	80 mm [ORS10]						21	17 (PL) / 2	2063 (CZ-S	5K)					

Metal door frames

METAL DOOR FRAME (BIG) [FD 11 / FD 12]



CONSTRUCTION

- welded frame
- ungalvanized plate with a thickness of 1.2 mm
- powder-coated frame in a choice of standard RAL colours
- 2 hinges in colour white zinc and a seal included
- universal mounting brackets for brick walls and plasterboard walls

DOOR FRAME FOR DOOR LEAVES IN WIDTH

- width of single doors "60" to "100"
- width of double doors "120" to "200"

RANGES OF WALL THICKNESS COVERING

- door frame FD 11-75 mm
- door frame FD 12—100 mm

DIMENSIONS

			single door (mm)					double door (mm)—ATTENTION: CHANGE OF DIMENSIONS							
		"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width	644	744	844	944	1044	1280	1380	1480	1580	1680	1780	1880	1980	2080
s2	width of the wall opening	670	770	870	970	1070	1306	1406	1506	1606	1706	1806	1906	2006	2106
s3	outer width of the door frame	696	796	896	996	1096	1332	1432	1532	1632	1732	1832	1932	2032	2132
s4	internal width of the door frame	600	700	800	900	1000	1236	1336	1436	1536	1636	1736	1836	1936	2036
h1	door leaf height							20)40						
h2	height of the wall opening							20)37						
h3	outer height of the door frame 2072														
h4	internal height of the door frame							20)24						

AVAILABLE RAL DECORS


9010-white 9016—white 8017—chocolate brown 7047—gray 7024—graphite 1001-beige


OPTIONS AT EXTRA CHARGE

- reinforcement for the self-closer
- · adapted for the electric door strike

METAL DOOR FRAME (SMALL) [FD 14]







CONSTRUCTION

- welded frame
- ungalvanized plate with a thickness of 1.2 mm
- powder-coated frame in a choice of standard RAL colours
- 2 hinges in colour white zinc and a seal included
- universal mounting brackets for brick walls and plasterboard walls

DOOR FRAME FOR DOOR LEAVES IN WIDTH width of single doors "60" to "100"


• width of double doors "120" to "200"

			single	door (mm) (mm)		double door (mm)—ATTENTION: CHANGE OF DIMENSIONS							ONS	
		"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width	644	744	844	944	1044	1280	1380	1480	1580	1680	1780	1880	1980	2080
s2	width of the wall opening	661	761	861	961	1061	1297	1397	1497	1597	1697	1797	1897	1997	2097
s3	souter width of the door frame	696	796	896	996	1096	1332	1432	1532	1632	1732	1832	1932	2032	2132
s4	internal width of the door frame	600	700	800	900	1000	1236	1336	1436	1536	1636	1736	1836	1936	2036
h1	door leaf height							20	40						
h2	height of the wall opening							20	38						
h3	outer height of the door frame							20	172						
h4	internal height of the door frame							20	24						

ADJUSTABLE METAL DOOR FRAME [FD 61-67]



s_2 s_4 s_4 s_1 s_3



CONSTRUCTION

DIMENSIONS

- 2-part frame, adjustable (adjustment range in 30 mm steps)
- ungalvanized plate with a thickness of 1.5 mm
- powder-coated frame in a choice of standard RAL colours
- 3 hinges in colour white zinc and a seal included
- universal mounting brackets for brick walls and plasterboard walls

DOOR FRAME FOR DOOR LEAVES IN WIDTH

- width of single doors "60" to "100"
- width of double doors "120" to "200"

2		single door (mm)					double door (mm)—ATTENTION: CHANGE OF DIMENSIONS								
		"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width	644	744	844	944	1044	1280	1380	1480	1580	1680	1780	1880	1980	2080
s2	width of the wall opening	683	783	883	983	1083	1316	1416	1516	1616	1716	1816	1916	2016	2116
s3	outer width of the door frame	716	816	916	1016	1116	1350	1450	1550	1650	1750	1850	1950	2050	2150
s4	internal width of the door frame	600	700	800	900	1000	1236	1336	1436	1536	1636	1736	1836	1936	2036
h1	door leaf height							20	40						
h2	height of the wall opening							20	65						
h3	outer height of the door frame							20	82						
h4	internal height of the door frame							20	24						





The SARA-PRO door frame introduces a brand new quality in interior decoration. Invisible to the naked eye, it makes the area lighter. Ideal for minimalist and modern interiors. Available in outer and inner versions.

Non-rebated door leaf for outer door frame and rebated door leaf for inner door frame is based on the NORMA DECOR 1 door leaf



no extra charge

CONSTRUCTION

- the frame is made of an MDF board
- board prepared for painting and wallpapering
- filling—"honeycomb" or tubular chipboard (optionally)
- frame with filling is covered with HDF boards on both sides
- width of single doors "60"-"90"

ADDITIONAL OPTIONS

- door without a keyhole
- ventilation undercut
- PVC ventilation sleeves
- cylinder lock insert 31/36
- filling—tubular chipboard
- automatic door bottom seal for door width "60"-"90"
- ventilation grid

STANDARD EQUIPMENT


- 2 hidden hinges
- magnetic lock for a standard key, a WC knob or a cylinder lock insert


DIMENSIONS OF A DOOR LEAF AND CONCEALED DOOR FRAME


			inner door f	frame (mm)	outer door frame (mm)						
		"60"	"70"	"80"	"90"	"60"	"70"	"80"	"90"		
s1	door leaf width	618	718	818	918	618	718	818	918		
s2	width of the wall opening	698	798	898	998	698	798	898	998		
s3	outer width of the door frame	688	788	888	988	688	788	888	988		
s4	internal width of the door frame	603	703	803	903	603	703	803	903		
h1	door leaf height		2027 (PL) / 1	975 (CZ-SK)			2017 (PL) / 1	1965 (CZ-SK)			
h2	height of the wall opening		2076 (PL) / 2	024 (CZ-SK)			2066 (PL) / 2	2014 (CZ-SK)			
h3	outer height of the door frame		2069 (PL) / 2	017 (CZ-SK)			2059 (PL) / 2	2007 (CZ-SK)			
h4	internal height of the door frame		2027 (PL) / 1	975 (CZ-SK)		2017 (PL) / 1965 (CZ-SK)					

EF

CONCEALED DOOR FRAME SARA-PRO-INNER








RIGHT

CONCEALED DOOR FRAME SARA-PRO-OUTER



Housing system



FEATURES


Metal frame housing (covering) allows the installation of new doors in the rooms where metal frames were mounted following the Polish standard (regarding dimensions) without having to remove these frames. The advantage of this solution is an easy installation with mounting foam, without dirty floors and walls, and the ability to mount standard foiled INVADO door leaves.

WIDTH OF THE DOOR FRAME FOR DOOR LEAVES

• width of single doors "60" to "90"

INTERNAL DIMENSIONS OF METAL DOOR FRAME (MM)

		"60"	"70"	"80"	"90"
s1	door leaf width	600	700	800	900
h1	door leaf height	20	025 (PL) / 1	975 (CZ-S	K)




RANGES OF WALL THICKNESS

• 60-94, 95-129, 130-199, 200-269

Housing system for metal door frames for walls thicker than 130 mm has an additional enlarging element.

For the range of 130–199—the enlarging element is 85 mm-wide. For the range of 200–269—the enlarging element is 155 mm-wide.





ACCESSORIES AND HANDLES

Accessories

FOILED AND MODULAR DOORS



caps for hinges (satinated chrome, chrome, black or golden) set for 1 piece of hinge



hinge



hidden hinge delivered with a door frame



cylinder lock insert



porthole (black or silver with satinated or transparent glass) included in the price of the door



automatic bottom door seal



aluminium threshold



door seal (black, white, gray, brown, beige)





ventilation sleeves metal round



ventilation sleeves metal square



ventilation grid

OPTIMO LINE





surcharge for changing the colour of the fittings—set: 2 hinges + strike plate + door leaf lock





edge band in a different colour than the door leaf surface (natural hamilton oak, alpine white or black)

KICK AND PUSH METAL PANELS

- material: polished stainless steel
- ventilation sleeves—diameter: 40 mm (depending on the width of the door leaf, a different number of ventilation sleeves are used: "60"—3 sleeves / "70"—4 sleeves / "80"—5 sleeves / "90"—"100"—6 sleeves)
- dimensions: width matched to the door leaf, height 300 mm, thickness 0.6 mm
- ventilation undercut—height: 15 mm;
- ventilation grid—dimensions: 430 x 110 mm.



BLACK IRONMONGERY FOR REBATED DOORS NEW



black lock (key / WC / cylinder insert)



strike plate for the block door frame



strike plate for the adjustable door frame

SLIDING SYSTEMS

black pivot hinge











hook lock WC / key

grip with folding key and a thimble

grip with WC knob and a thimble

grip and

a thimble

strike plate

soft-close hardware for sliding door



door seal

profiles and architraves



brush



rail cover



bumper

TECHNICAL DOORS



cylinder lock (Guardia)



self-closer (Guardia / Ignis)



cylinder lock insert (Guardia / Ignis)



intumescent seals (Guardia)



cylinder lock insert with a WILKA knob (Egida)



hinge with regulation (Guardia)



automatic bottom door seal (Guardia / Egida)



handle QUEBECK (TYTAN / INOX) (Egida)




panoramic viewfinder (Guardia / Egida)



handle ROYAL (INOX) (Egida)

www.invado.pl




136



	with escutcheon for repeatable key	with escutcheon for cylinder lock insert	with escutcheon for WC lock	COLOURS:
handle SPARK photo: satinated nickel	0	1		satinated nickel
handle TOTAL-Q photo: glossy chrome]	?		black matt chrome glossy chrome
handle ENTRA photo: anthracite/chrome				satinated nickel/chrome
handle FLIP photo: anthracite/chrome				satinated nickel/chrome
handle GIUSSY photo: nickel/chrome	0	0		brown grafiatto nickel/chrome
handle INVADO photo: nickel/chrome	0	0	6	nickel/chrome
handle PRESTO photo: nickel/chrome	0	0		nickel/chrome
handle UNO-R photo: stainless steel		\bigcirc		stainless steel (inox)
			~	
handle UNO photo: stainless steel			~	stainless steel (inox)





MODEL P125



MODEL P127



ADDITIONAL OPTIONS

- finishing element 20 x 20 x 120 mm
- clips—30 pcs/package

NOTE: The length of a single skirting is 2.4 m. The skirtings are packed and sold in sets of 5. The prices below are for 1 pc.




MODEL P129 / P402 / P403









Distributor's stamp:

A company of Arbonia Group

All information in the catalogue do not constitute an offer within the meaning of the Civil Code and are published for informational purposes only. Manufacturer reserves the right to make changes.

Note! Due to the printing technique the colors of the products presented in the catalogue may differ from the original. All rights reserved. Copying and publication of this catalogue on web sites and in other media without the written consent from INVADO Sp. z.o. is prohibited.